



General

| | |
|-----------------------|-------------------------|
| Product number | 100013 |
| Housing material | PC-GF10 |
| Housing colour | RAL 9005 |
| Mounting | 54E1, 64E1, S49 rail |
| Fixing | Stainless steel bracket |
| Ingress protection | IP66/68 |
| IK rating | IK10 |
| Operating temperature | -40...70°C |
| Country of origin | the Netherlands |
| Warranty | 5 years |

Electrical

| | |
|-------------------|-----------------------|
| Protection class | III |
| Operating voltage | 36 Vdc |
| Power | 2,0 W |
| Power supply | External power supply |

Photometric data

| | |
|-------------------------|---------------------|
| Light source | CREE XP-G3 |
| Colour temperature | 3000 K |
| Colour rendering index | CRI>70 |
| Colour tolerance | 3 SDCM |
| Number of LEDs | 2 |
| Light distributor | Lens |
| Light distribution | Asymmetric beam |
| Luminous flux | 119 lm |
| Efficacy | 60 lm/W |
| Life expectancy at 25°C | 60.000 hrs (L80B10) |

Packaging

| | |
|------------------|---------------|
| Unit | Cardboard box |
| Content quantity | 20 per box |
| Length | 280 mm |
| Width | 145 mm |
| Height | 170 mm |
| Weight | 6 kg |

Dimensions and weights

| | |
|--------|--------|
| Length | 138 mm |
| Width | 28 mm |
| Height | 80 mm |
| Weight | 280 g |

